



电解抛光腐蚀机

QATCH 1000

Qetch 1000是一款通过触屏界面直观操作的全自动电解抛光腐蚀机。具有独立的抛光刻蚀单元和控制单元，并可以在通风橱中使用。

无需知晓试样组织情况，通过扫描功能即可显示材料的电流-电压特征曲线。将电解液储存在1升体积的独立电解槽中进行封盖储存，工作时通过整体更换的方式来更换电解液，极大地方便了抛光刻蚀单元的操作。设备的清洁可以采用水，通过清洗程序完成。

优点

- | 自动电化学抛光/腐蚀装置
- | QATM软件控制的触摸式操作屏
- | 可储存200个程序，并可设置密码
- | 实时显示电流和电压
- | 输出电压和过程持续时间可调

电解抛光腐蚀机 QETCH 1000

技术参数

连接电源	2 kVA
最大电压	90 V DC
最大流量	14 A
抛光时间	1 sec - 25 min
腐蚀时间	1 sec - 5 min
宽 x 高 x 深	330 x 220 x 400mm
重量	~ 7 kg

www.qatm.cn/qetch-1000

ORDER DATA

BASIC EQUIPMENT

MACHINE (ALL ITEMS REQUIRED)

M6202000  Qetch 1000 (Kristall 680) Base machine

A6202003 Qetch 1000 (Kristall 680) polishing and etching unit

POWER SUPPLY (1 ITEM REQUIRED)

A6202000 Qetch 1000 power supply 220-240V/50/60Hz (1Ph/N/PE)

A6202001 Qetch 1000 power supply 110-120V/50/60Hz (1Ph/N/PE)

ELECTRICAL BOARD FOR SECOND ETCHING CELL (TO BE ORDERED WITH THE MACHINE)

A6202005 Qetch 1000 connection extension

OPTIONS (CAN BE ORDERED SEPARATELY)

A6202004 External etching unit

Z6202001 Set of masks

Z6202002 Electrolyte vessel

Z6202003 Connection set Qetch 1000 (Kristall 680)